

There's room for careful drying and easy installation in every home.



Two Models, Vented and Condensation

Siemens offers two versions of our compact, efficient clothes dryers. Between them, you'll have all the installation options you need.

Condensation Dryer Requires No Ducting

The vented dryer offers two venting options, left or rear, while the condensation dryer requires no venting at all. That means no ducting or vents to install, and unlimited placement options.

Specialty Fabric Cycles

The compact ultraStack™ dryers feature specialty cycles that can handle the most varied wardrobes. The vented dryer features 9 auto dry cycles with a Delicates cycle, while the condensation dryer features 11 auto dry cycles that include Wool, Quick and Low Heat.

Large Capacity

The 3.9 cubic foot capacity can dry 14 pairs of jeans at once. And the 165° door swing makes getting them in and out easy.

See-Through Door

Besides adding to the tasteful design, the see-through doors let users see at a glance if the dry cycle is finished.

German Engineering

The ultraStack™ dryers are engineered to Siemens' exacting standards. No detail of their design or manufacture is overlooked. It's why the ultraStack™ line of dryers is one of Europe's best selling.





ultraStack™ 24" Stackable Dryers

The future moving in.

SIEMENS



Condensation Dryer
WT46E300US shown with
optional 11" Pedestal WZ20460



Dryer Dimensions

A	33-3/32-34-3/16"	G	33-5/32"
B	23-24-3/16"	H	1-3/16"
C	23-5/8"	I	5-3/16"
D	17-23/32"	J	19/32"
E	40-15/16"	K	7-23/32"
F	24-5/8"	L	4-23/32"

ultraStack™ 24" Stackable Dryers Specifications

	ultraStack™ Vented Electric Dryer WT36V100US	ultraStack™ Condensation Electric Dryer WT46E300US
Drying Performance		
Total Cycles	9	11
Gentle and Efficient Drying Motion	■	■
Temperature Sensor for Gentle Heat	■	■
Digital Moisture Sensor	■	■
Dry Cycles/Settings		
Timed Dry	Warm 20 min., Cold 20 min.	Warm 40 min., Warm 20 min.
Delicates	■	
Low Heat		■
Wool		■
Quick		■
Less Ironing		■
Anti-Wrinkle Function	1 hr.	2 hr.
Regular/Cotton Settings	Damp Dry, Regular Dry, Very Dry, Extra Dry	Damp Dry, Regular Dry, Very Dry, Extra Dry
Permanent Press Settings	Damp Dry, Regular Dry, Very Dry	Damp Dry, Regular Dry, Very Dry
Convenience		
Capacity (IEC)	3.9 cu. ft.	3.9 cu. ft.
Door Angle	165°	165°
See-Through Door	■	■
Left and Rear Venting	■	
No Ducting Required		■
Electronic Touch Controls	■	■
Door Lock with Auto Circuit Break	■	■
Snag-Proof, Rust-Proof Stainless Steel Structured Drum	■	■
Lint Filter Indicator	■	■
Delay Start		19 hr.
Optional 11" Pedestal with Storage Drawer and Fold-Up Laundry Basket (WZ20460)	■	■
Optional Stacking Kit with Pull-Out Tray (WZ20300UC)	■	■
Optional Stacking Kit without Pull-Out Tray (WZ20310UC)	■	■
Efficiency		
Silence Rating (IEC)	67 dBA	67 dBA
Design		
Display		LED
Door Hinged on Left	■	■
Bull's Eye Ring	Silver	Silver
Finish Color	White	White
Durable Mekalit Work Top	■	■
Technical		
Supply Voltage	208/240 V	208/240 V
Frequency	60Hz	60Hz
Amperage	13A	13A
UL Approved	■	■

1-888-4-SIEMENS • In the US: siemens-home.com

©2008 BSH Home Appliances Corporation. All rights reserved. Specifications subject to change without notice.

Dryers are UL approved. For immediate critical installation dimensions by fax, use your handset and call 775-833-3600.

Warranty: BSH warrants that its laundry products are free from defects in materials and workmanship for a period of 1 year for labor, 2 years for parts, 2 years on all electronic components, lifetime on stainless steel drum. Certain limitations apply. See Manufacturer's Limited Warranty for details. SE_PW_G11_1_001